

COUCHETTE

Type: 248.5 | Bvcmz

RDC

Zugkraft, die verbindet.

TECHNICAL SPECIFICATIONS:

Length over buffer:	26 400 mm
Car body length:	26 100 mm
Car body width:	2 825 mm
Height above top of rail:	4 050 mm
Pivot spacing:	19 000 mm
Axle position:	21 500 mm
Axle position in the bogie:	2 500 mm
Bogie design:	Minden-Deutz 367
Tare weight:	47 t
Maximum speed:	200 km/h
First/second class seats:	-/60
Compartments:	10 compartments 2nd class; 1 companion compartment
Air conditioning:	Air conditioner plus sliding window
Toilets:	2, closed system
Washrooms:	3
Service room:	1
Brake design:	<R> KE-GPR-Mg (D) [ep] [NBÜ]
Brake weights:	<R>+Mg 109 t, <R> 77 t, R 74 t, P 57 t, G 44 t
Heating design:	Klimae
Energy supply:	Central power supply
Batteries:	24 V, 385 Ah
Construction year:	1999 - 2000 (ex factory); 2005 - 2006 (ex Bvcmz 248.7)
Manufacturer	AW Halberstadt (ex factory); AW Neumünster (ex Bvcmz 248.7)

OUR FLEET:

61 80 50 - 91 011-5	Bvcmz	248.5
61 80 50 - 91 051-1	Bvcmz	248.5
61 80 50 - 91 001-1	Bvcmz	248.5
61 80 50 - 91 026-3	Bvcmz	248.5
61 80 50 - 91 028-9	Bvcmz	248.5
61 80 50 - 91 029-7	Bvcmz	248.5
61 80 50 - 91 031-3	Bvcmz	248.5
61 80 50 - 91 034-7	Bvcmz	248.5
61 80 50 - 91 035-4	Bvcmz	248.5
61 80 50 - 91 036-2	Bvcmz	248.5
61 80 50 - 91 043-8	Bvcmz	248.5

61 80 50 - 91 044-6	Bvcmz	248.5
61 80 50 - 91 046-1	Bvcmz	248.5
61 80 50 - 91 047-9	Bvcmz	248.5
61 80 50 - 91 048-7	Bvcmz	248.5
61 80 50 - 91 002-9	Bvcmz	248.5
61 80 50 - 91 003-7	Bvcmz	248.5
61 80 50 - 91 019-3	Bvcmz	248.5
61 80 50 - 91 020-1	Bvcmz	248.5
61 80 50 - 91 024-3	Bvcmz	248.5
61 80 50 - 91 016-4	Bvcmz	248.5

ADDITIONAL INFORMATION:

The cars can be used internationally according to RIC standard and are compatible with 1000V, 1500V and 3000V traction current systems. All compartments have two sockets and 4 USB charging stations. WLAN can be ordered additionally.

We offer an optional conversion of the companion compartment to a galley with microwave, a refrigeration unit for gastronomic trolley and a supply of coffee, tea and cocoa specialties.

